



Model: SQP220 (S)		
Standby Power (50Hz)	176KVA/220KW	
Prime Power(50Hz)	160KVA/200KW	

Standard Features

• Engine: Perkins 1506A-E88TAG1

Charge Alternator: 24V

Governer: Electronic

Generator: Stamford UCI274H

Single Bearing Alternator IP23

· Insulation Class H/H

· Genuine radiator with engine driven fan

Skid and vibration isolators

Dry type air filter

Main line circuit breaker (Below 500KVA)

12V battery and cable

User's manual



Weight And Dimensions			
Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	2900mmx900mmx1536mm	1830	
Silent type	3600mmx1333mmx2040mm	2959	

Genera	ator Ra	atings			
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	176/220	160/200

Criterion

• Generator sets: GB/T2820-1997, ISO9001: 2008

Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359

Diesel Engine: ISO3046, DIN6271





SANO Sand Power

Engine Data		
Manufacturer/Model	Perkins 1506A-E88TAG1	
No.of Cylinders	6	
Displacement	8.8L	
 Bore and Stroke 	112*149 (mm)	
 Compression ratio 	16.1:1	
Rated RPM	1500rpm	
 Max.standby power at rated 1500RPM 	196KW	
 Aspiration 	Turbocharged aftercooled	
Governor Type	Electronic	
 Exhaust Gas Flow @Standby Rating 	31.9m³/min	
 Exhaust Temperature @Standby Rating 	470℃	
 Intake Air Flow@Standby Rating 	13.5m ³ /min	
5 10 I	Recommended fuel to conform to BS 2869 1998 CLASS	
Fuel System	A2 or BSEN590	
• 100%(Prime Power) Load	44.6Liter/H	
Lubrication System Min. capacity	39L	
Total Coolant Capacity	29.6L	

Alternator Data		
 Manufacture/Type 	Stamford/UCI274H	
 Number of phase power 	3	
 Factor 	0.8	
Pole Number	4	_
Bearing Number	1	
Exciter Type	Brushless, self-excited	_
 Insulation Class 	H/H	_
Protection	IP23	_

Control Panel



- Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 7320 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.
- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.
- RS232 or 485 interface which can communicate with PC to realize remote operation.







• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	Anti Condensation HeaterDrop CT (For Paralleling)	•	Remote Control PanelAuto Transfer Switch (ATS)Paralleling System
			 Electricity Output Cabinet

Others

- · Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts















Warranty







SANO Sanq Power

- Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Perkins gensets enjoy world-wide united Warranty from Perkins engine agency or service centre at the client's local side.
- Service and parts are available from Guangzhou Sanq Power Equipment Co., Ltd or our distributors in your location.



