



Model: SQP220 (S)	
Standby Power (50Hz)	220KVA/176KW
Prime Power(50Hz)	200KVA/160KW

Standard Features

• Engine: Perkins 1106A-70TAG4

Charge Alternator: 24V

Governer: Electronic

Generator: Stamford UCI274H

Single Bearing Alternator IP23

· Insulation Class H/H

· Genuine radiator with engine driven fan

Skid and vibration isolators

Dry type air filter

Main line circuit breaker (Below 500KVA)

12V battery and cable

User's manual



Weight And Dimensions			
Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	2900mmx900mmx1536mm	1830	
Silent type	3600mmx1333mmx2040mm	2959	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	220/176	200/160

Criterion

• Generator sets: GB/T2820-1997, ISO9001: 2008

Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359

Diesel Engine: ISO3046, DIN6271







SANO Sand Power

Engine Data	
Manufacturer/Model	Perkins 1106A-70TAG4
No.of Cylinders	6
Displacement	7.01L
Bore and Stroke	105*135mm)
Compression ratio	16:1
Rated RPM	1500rpm
 Max.standby power at rated 1500RPM 	196.3KW
 Aspiration 	Turbocharged aftercooled
Governor Type	Electronic
 Exhaust Gas Flow @Standby Rating 	36.8m³/min
 Exhaust Temperature @Standby Rating 	550℃
 Intake Air Flow@Standby Rating 	13.2m³/min
Fuel System	Rotary type pump
• 100%(Prime Power) Load	45.8Liter/H
 Lubrication System Min. capacity 	12.5L
Total Coolant Capacity	21L

Alternator Data		
Manufacture/Type	Stamford/UCI274H	
 Number of phase power 	3	
Factor	0.8	
Pole Number	4	
Bearing Number	1	
Exciter Type	Brushless, self-excited	
Insulation Class	H/H	
Protection	IP23	

Control Panel



- Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 6020 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.
- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.





Data Sheet



• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Engine	Alternator	Fuel System	Control System
• Pre-heater	Anti Condensation HeaterDrop CT (For Paralleling)	3	Remote Control PanelAuto Transfer Switch (ATS)Paralleling System
			• Electricity Output Cabinet

Others

- Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts



















SANO Sanq Power

Data Sheet

Warranty

- Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Perkins gensets enjoy world-wide united Warranty from Perkins engine agency or service centre at the client's local side.
- Service and parts are available from Guangzhou Sanq Power Equipment Co., Ltd or our distributors in your location.



