QSAND Sanq Power

Model: SQP250 (S)	
-------------------	--

Standby Power (50Hz)	200KVA/250KW	
Prime Power(50Hz)	180KVA/225KW	

Standard Features

- Engine: Perkins 1506A-E88TAG2
- Charge Alternator: 24V
- Governer: Electronic
- Generator: Stamford UCDI274J
- Single Bearing Alternator IP23
- Insulation Class H/H
- Genuine radiator with engine driven fan
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker (Below 500KVA)
- 12V battery and cable
- User's manual

Weight And Dimensions

Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	3000mmx1200mmx2000mm	2760	
Silent type	4100mmx1490mmx2000mm	4500	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	200/250	180/225

Criterion

- Generator sets: GB/T2820-1997, ISO9001: 2008
- Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359
- Diesel Engine: ISO3046, DIN6271







QSAND Sanq Power

Engine Data

3	
Manufacturer/Model	Perkins 1506A-E88TAG2
No.of Cylinders	6
Displacement	8.8L
Bore and Stroke	112*149 (mm)
Compression ratio	16.1:1
Rated RPM	1500rpm
 Max.standby power at rated 1500RPM 	222KW
Aspiration	Turbocharged aftercooled
Governor Type	Electronic
 Exhaust Gas Flow @Standby Rating 	35.7m ³ /min
 Exhaust Temperature @Standby Rating 	475℃
 Intake Air Flow@Standby Rating 	15m ³ /min
	Recommended fuel to conform to BS 2869 1998 CLASS
Fuel System	A2 or BSEN590
100%(Prime Power) Load	48.6Liter/H
Lubrication System Min. capacity	39L
Total Coolant Capacity	29.6L

Alternator Data

Manufacture/Type	Stamford/UCDI274J	
 Number of phase power 	3	
• Factor	0.8	
Pole Number	4	
Bearing Number	1	
Exciter Type	Brushless, self-excited	
Insulation Class	H/H	
Protection	IP23	

Control Panel



• Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 7320 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.

- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.

• RS232 or 485 interface which can communicate with PC to realize remote operation.









• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Others

Engine	Alternator	Fuel System	Control System
Pre-heater	 Anti Condensation Heater Drop CT (For Paralleling) 	5	 Remote Control Panel Auto Transfer Switch (ATS) Paralleling System

Electricity Output Cabinet

<image>

Warranty





QSAND Sanq Power

Data Sheet

• Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Perkins gensets enjoy world-wide united Warranty from Perkins engine agency or service centre at the client's local side.

• Service and parts are available from Guangzhou Sanq Power Equipment Co.,Ltd or our distributors in your location.





