QSAND Sanq Power

Model · SOP88 (S)

Standby Power (50Hz)	88KVA/70KW
Prime Power(50Hz)	80KVA/64KW

Standard Features

- Engine: Perkins 1104A-44TG2
- Charge Alternator: 24V
- Governer: Electronic
- Generator: Stamford UCI224G
- Single Bearing Alternator IP23
- Insulation Class H/H
- Genuine radiator with engine driven fan
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker (Below 500KVA)
- 12V battery and cable
- User's manual

Weight And Dimensions

Genset	Dimensions(LxWxH)	Weight (KG)	
Open type 1750mmx850mmx1300mm		1037	
Silent type	2450mmx1000mmx1650mm	1560	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	50	3	0.8	88/70	80/64

Criterion

- Generator sets: GB/T2820-1997, ISO9001: 2008
- Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359
- Diesel Engine: ISO3046, DIN6271







QSAND Sanq Power

Engine Data

Manufacturer/Model	Perkins 1104A-44TG2
No.of Cylinders	4
Displacement	4.4L
Bore and Stroke	105*127(mm)
Compression ratio	17.25:1
Rated RPM	1500rpm
 Max.standby power at rated 1500RPM 	79.1KW
Aspiration	Turbocharged
Governor Type	Electronic
 Exhaust Gas Flow @Standby Rating 	13.3m ³ /min
 Exhaust Temperature @Standby Rating 	580°C
 Intake Air Flow@Standby Rating 	5.14m ³ /min
Fuel System	Rotary type pump
100%(Prime Power) Load	18.7Liter/H
 Lubrication System Min. capacity 	5.5L
Total Coolant Capacity	13.0L

Stamford/UCI224G	
3	
0.8	
4	
1	
Brushless, self-excited	
H/H	
IP23	
	3 0.8 4 1 Brushless, self-excited H/H

Control Panel



• Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 6020 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.

• Features: receive remote output signal from ATS and realize auto start and stop of generators.

• Auto Mains Failure controller, can realize further more can detect ATS and control directly.









• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	 Anti Condensation Heater Drop CT (For Paralleling) 	5	 Remote Control Panel Auto Transfer Switch (ATS) Paralleling System

Electricity Output Cabinet

Others

- Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts









QSAND Sanq Power

Warranty

• Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Perkins gensets enjoy world-wide united Warranty from Perkins engine agency or service centre at the client's local side.

• Service and parts are available from Guangzhou Sanq Power Equipment Co., Ltd or our distributors in your location.





