



Model: SQP12-6 (S)		
Standby Power (60Hz)	12KVA/10KW	
Prime Power(60Hz)	11KVA/8.8KW	

Standard Features

• Engine: Perkins 403D-11G

Charge Alternator: 24V

Governer: Mechanical

Generator: Stamford PI044E

Single Bearing Alternator IP23

· Insulation Class H/H

· Genuine radiator with engine driven fan

Skid and vibration isolators

Dry type air filter

Main line circuit breaker (Below 500KVA)

12V battery and cable

User's manual



Weight And Dimensions			
Genset	Dimensions(LxWxH)	Weight (KG)	
Open type	1500mmx650mmx1225mm	436	
Silent type	2200mmx1033mmx1306mm	946	

Generator Ratings					
Voltage	Hz	Phase	Power Factor	Standby (KVA/KW)	Prime (KVA/KW)
400/230	60	3	0.8	12/10	11/8.8

Criterion

• Generator sets: GB/T2820-1997, ISO9001: 2008

Alternator: BS5000, VDE0530, NEMA MG1-32, IEC34, CSAC22.2-100, AS1359

Diesel Engine: ISO3046, DIN6271







SANO Sanq Power

Engine Data	
Manufacturer/Model	Perkins 403D-11G
 No.of Cylinders 	3
Displacement	1.131L
Bore and Stroke	77*81 (mm)
 Compression ratio 	23:1
Rated RPM	1800rpm
 Max.standby power at rated 1800RPM 	11.4KW
Aspiration	Naturally aspirated
Governor Type	Mechanical
 Exhaust Gas Flow @Standby Rating 	2.4m³/min
 Exhaust Temperature @Standby Rating 	515℃
 Intake Air Flow@Standby Rating 	0.9m³/min
Fuel System	Indirect injection
 100%(Prime Power) Load 	3.0Liter/H
 Lubrication System Min. capacity 	3.4L
 Total Coolant Capacity 	5.2L

Alternator Data		
Manufacture/Type	Stamford/PI044E	
 Number of phase power 	3	
 Factor 	0.8	
Pole Number	4	
Bearing Number	1	
Exciter Type	Brushless, self-excited	
Insulation Class	H/H	
Protection	IP23	

Control Panel



- Auto Module Control Panel, usually adopt control module of UK Deepsea DSE 6020 or Equal, is the configuration for nobody on duty generators control, This kind of panel adopts auto module control system, with large LCD display to show the menu.
- Features: receive remote output signal from ATS and realize auto start and stop of generators.
- Auto Mains Failure controller, can realize further more can detect ATS and control directly.







• Automatic Parallel Control Panel usually adopting intelligent control module of UK Deepsea DSE8610 or equal, this new automatic parallel system is inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined togethe rwith the generator, which is very reliable. One generator, one panel. The panel can be used both for single genset working or Gensets Parallel working. This kind of panel also can be used to parallel generator when the capability of the power plant needs to be enlarged in the future.

Optional

Engine	Alternator	Fuel System	Control System
Pre-heater	Anti Condensation HeaterDrop CT (For Paralleling)	•	Remote Control PanelAuto Transfer Switch (ATS)Paralleling System
			 Electricity Output Cabinet

Others

- · Rainproof Type
- Soundproof Type
- Trailer Type
- Container Type
- Spare Parts















Warranty







SANO Sanq Power

- Warranty is according to our standard conditions: 12 months or 1,200 running hours, subject to the earlier one. And what's more, Perkins gensets enjoy world-wide united Warranty from Perkins engine agency or service centre at the client's local side.
- Service and parts are available from Guangzhou Sanq Power Equipment Co.,Ltd or our distributors in your location.



